





Ultra-Compact Lightweight Design Easy to Install NOW with VersaFlo^M Integrated Bypass

Jandy

JXi™ Swimming Pool & Spa Gas Heater

The Total Package

The JXi heater sets the standard in pool and spa heating technology with its ultra-compact size, lightweight design, and installation flexibility, making it a top choice for pool professionals and pool owners everywhere. The high-efficiency, low-NOx JXi is available in three BTU sizes, 200K, 260K, 399K, and offered in both natural and propane gas models. Now also available with VersaFlo[™] Integrated Bypass technology for maximum hydraulic efficiency and energy savings.

Fastest Installation

Pro-driven features for the fastest, most customer-friendly installation include:

Ultra-Compact

2' x 2' footprint for small space requirements and maximum installation flexibility**

Lightweight Design

Weighs less than 126 pounds unpackaged for easy maneuverability and transport.

Best Retrofit Option

Plumbing flexibility for quick Mastertemp[®] and Max-E-Therm[®] replacement that requires no plumbing adjustments***

NEW! Easy VersaFlo Installation

The flow bypass valve is integrated into the JXi's header, requiring no external plumbing modifications. Available on select models only.



Refer to JXi manual for proper heater clearances that may apply. *Please see Easy Replacement section on next page.

Energy Efficient

rating and **low-NOx** design surpasses strict DOE Energy

83% thermal efficiency

Éfficiency requirements.

Automation-Ready

Convenience built in. AquaLink/iAquaLink-compatible with its RS485 interface.





Features



Ultra-Compact Lightweight Design

Easy to store, transport, and install, JXi™ is 38% lighter with a 28% smaller footprint. *Compared to major competitor models



Flexible Installation

180° rotatable top so you never need to rotate headers. Electrical panel flips up for ease of service.



Versa Plumb[®]-Ready

Installation in the VersaPlumb system* reduces plumbing costs and increases energy efficiency, all using the smallest footprint available. *Sweep elbow included in all JXi models

NEW

Available VersaFlo Integrated Bypass for Maximum Hydraulic and Energy Efficiency


- >> Up to 20 percent additional energy savings*
- VersaFlo bypass is integrated into the JXi header, requiring no external plumbing modifications.
- Automatic actuation of bypass is based on call for heat and does not require human interaction

* versus similar system without VersaFlo




Heat Mode

While heating, water flow is directed through the heat exchanger and heated water is returned to the pool/spa.



Bypass Mode

VersaFlo Integrated Bypass diverts water flow around the heat exchanger when not heating water.



Additional Features



Corrosion-resistant stainless steel header bar for extreme heat exchanger durability.



Venturi-driven air and gas mix for enhanced performance.




Reliable, balanced flow and temperature control with thermal regulator valve.




Differentiated limit switches meet applicable product safety standards.



Corrosion-resistant temperature sensors for reliable operation.



INLET SIDE



NOTE: Dimensions are identical on all heater models

Available in the Following Models

| | | | | Vent | | | | Minimum | Maximum |
|-------------------------------|----------------------------|-------------|-------|------------|-------|--------|----------|---------|---------|
| Model # | Firing Rate | Gas Type | Width | Diameter* | Depth | Height | Weight | GPM | GPM |
| JXi200N | 200K BTU | Natural Gas | 22.9" | 6" (15 cm) | 22.1" | 26.5" | 117 lbs. | 30 | 100 |
| JXi260N | 260K BTU | Natural Gas | 22.9" | 7" (18 cm) | 22.1" | 26.5" | 120 lbs. | 30 | 100 |
| JXi400N | 399K BTU | Natural Gas | 22.9" | 8" (20 cm) | 22.1" | 26.5" | 126 lbs. | 30 | 100 |
| JXi200P | 200K BTU | Propane | 22.9" | 6" (15 cm) | 22.1" | 26.5" | 117 lbs. | 30 | 100 |
| JXi260P | 260K BTU | Propane | 22.9" | 7" (18 cm) | 22.1" | 26.5" | 120 lbs. | 30 | 100 |
| JXi400P | 399K BTU | Propane | 22.9" | 8" (20 cm) | 22.1" | 26.5" | 126 lbs. | 30 | 100 |
| JXi400NK w/VersaFlo | 400K BTU | Natural Gas | 22.9" | 8" (20 cm) | 22.1" | 26.5" | 126 lbs. | 30 | 100 |
| JXiVFKIT | JXi VersaFlo Accessory Kit | | | | | | | | |

*Minimum vent pipe size for Category I installations.

2 units per pallet

Zodiac Pool Systems, Inc.

2620 Commerce Way, Vista, CA 92081 1.800.822.7933 | www.jandy.com

Zodiac Pool Systems Canada, Inc.

2115 South Service Road West, Unit #3, Oakville, ON L6L 5W2 1.888.647.4004 | www.ZodiacPoolSystems.ca